



ONE FOR ALL

ELASTIC WIPE CARE



CLEANING AND CARE

- FOR ALL RESILIENT FLOORING
- FOR CONSTRUCTION END AND MAINTENANCE CLEANING

- pH neutral
- Care and maintenance in one work operation
- Slip resistant, tread-secure and dirt-repellent
- Very high cleaning power
- No residues

RZ | A Brand of Uzin Utz AG



RZ Elastic Wipe Care

Care and maintenance product for all resilient flooring, factory coated resilient flooring (LVT's), and all resilient flooring coated with RZ Elastic Sealer

RZ Elastic Wipe Care is a special Care and Maintenance Product, designed for construction end cleaning, as well as maintenance cleaning of all resilient flooring.

Especially suitable for the surface treatment of:

- ▶ Factory coated elastic flooring
- ▶ Vinyl
- ▶ CV
- ▶ Rubber
- ▶ Natural and artificial stone

Important for all LVT's:

RZ Elastic Wipe Care is especially designed for the requirements of polyurethane coated resilient flooring. Particularly suited for construction-final cleaning and maintenance-cleaning of these flooring.

Product Properties / Benefits:

- ▶ High dirt-dissolving capacity
- ▶ Slip resistant
- ▶ Tread-secure
- ▶ Cleaning and maintenance in one work operation
- ▶ Dirt-repellent
- ▶ Highly concentrated , dilute with water 1:200

Technical data:

Container type	Canister / Bottle (PE)
Delivery size	800 ml / 10 ltr.
Shelf life	unlimited
Maintenance cleaning:	
Consumption	50 ml / 10 ltr. water
Processing temp.	18 - 25 Co
Passable	After drying
pH-value	7,2
Giscode	GU 50



Preparation:

Sweep off loose dirt or light soiling. Remove coarse dirt thoroughly first.

Processing

Construction end cleaning:

1. Dilute RZ 181 Elastic Wipe Care 1:10 with water
2. Wet surface thoroughly and allow to act for a short time.
3. Scrub lightly according to requirement or run over surface repeatedly with RZ Single-Disc Machine.
4. Collect slops

Maintenance cleaning:

1. Dilute RZ Elastic Wipe Care 1:200 with water
2. Wet surface thoroughly and wipe with a synthetic fibre mop.
3. Allow residual moisture to dry.

Important Notes:

- ▶ Stable in original container with storage under uniform conditions for an unlimited period.
- ▶ It is important to protect against frost or strongly fluctuating temperatures. Tightly close off containers already opened.
- ▶ Optimal processing at low air humidity (approx. 65%) and normal room temperatures (18 - 25 degrees centigrade).
- ▶ Regular maintenance care improves the optics and service life duration of the ex-works applied PU/PUR coating. Include these coatings in the maintenance cleaning only for so long until the first appearances of wear occur. Then, where appropriate, maintenance with RZ Elastic Sealer.
- ▶ Consider the RZ cleaning and maintenance instructions

Work and environment protection:

Non-flammable, no irritant effects and not environmentally dangerous. It is possible that the contained and designated components of the perfumes, as well as the preservatives, can cause sensitizing or allergies with certain groups of persons.

Disposal:

Do not allow to enter undiluted into the sewage system, into water bodies or into the soil. Rinse out residue-emptied containers with a little water and dispose of as recycling-capable containers, in accordance with the local / official directives (DSD). The specifications are based on our experience and careful investigations. The quality of your work depends on professional construction site evaluation and product use by yourself. If in doubt, conduct a small sample test or obtain technical advice. The directions for use on the containers are to be strictly adhered to. With the issue of this product datasheet, all preceding product datasheets lose their validity.

09.02.2009 | FM